

Index

- absorptance, 31, 49, 54, 55, 72–73, 81, 85, 86, 100, 121, 125, 128, 169, 172–179, 187, 207, 339, 346, 351, 485, 557, 561–563, 596, 769–773
 - degradation of, **143–158**
 - of surface finishes, **139–143, 791–801**
- absorptance-to-emittance ratio, 142, 166, 187, 331
- acceptance test, 457, **709–734, 746**
- acquisition reform, 709, 710
- aerobraking (aerocapture), 13–14, 60–63, 89–92
- aerogel. See insulation, aerogel
- albedo, 40, 45–49, 66, 73, 86, 91, 339–340, 536, 555–563, 648, 666
 - of Earth, 21–31
 - of planets and moon, **50–60**
- analysis, 532–536, **537–575**
 - of doublers, 291–303
 - of heat exchangers, 424–431
 - of heat pipes, 496–500
 - of instruments (example), 552–571
 - of louvers, 335–346
 - of margins, 572–575, 718–725
 - of phase-change material, 380–395
 - of pumped loops, 407–424
 - of radiators, 217–220
 - of space shuttle, 684–697
 - of thermoelectric coolers, 481–487
- analysis codes, **576–596**
 - ATRIUM, 591, 596
 - FEMAP, 592
 - IDEAS, 589, 590, 592, 594
 - ITAS, 592, 594
 - NEVADA, 561, 563, 568, 594, 595
 - SINAPS, 592
 - SINDA, 443, 444, 518, 519, 540, 552, 561, 563, 568, **575–586**, 589, 590–592, 594, 686
 - SOAP, 591
 - SSPTA, 592
 - TAS, 591–596
 - Thermal Desktop, 443, 519, 592
 - THERMICA, 592, 594
 - TRASYS, 561, 590–595, 686
 - TSS, 590, 592, 596
- antenna, 1, 2, 18, 64, 66, **79–81**, 92, 96, 131, 134, 137, 356, 523, 534, 729, 746, 753–754, 761
- apogee, 7, 10, **38–40**, 47, 61, 66, 74
- ascending node, **38–40**
- atomic oxygen, 145, 147, 161, 180, 768
- attitude control, 3, 73, 83, 145, 450, 530, 536, 640, 710
- batt insulation. See insulation, batt
- battery, 2, **77–79**, 95, 100, 103, 104, 107, 310, 449, 533, 536, 710, 729, 730, 746, 756, 762, 765, 780, 784, 785
- bearings, 135, 241, 247, **318–320**, 347, 418, 447, 453, 464, 552–554, 561, 567
- beta angle, 30, **40–44**, 96, 98, 537, 553–557, 561, 563, 673, 681–682, 687
- Beta cloth, 140, 144, 154, 170–171, 177, 193, 679
- black Kapton, 110, 114, 140, 146, 154, 158, 170, 187, 190, 194
- blankets. See insulation, multilayer
- body-mounted radiator, 209–212
- bolted joints, 261–265, 276
- boundary node, 541
- burn-in test, 714, 736–737, 741
- bus, 1, 66, 89, 91, 95, 211, 228–232, 237, 240, 355, 646, 661, 719, 747, 748, 750, 760
- Calgraph, 278, 281–284
- capacitance, 216, 353, 358, 376, 427, 429, **537–546**, 552, 567–568, 578, 581, 583, 596, 639, 697, 783
- capillary pumped loop, 209, 355, 495–496, **502–520**, 533, 719, 781–782
- Cargo Integration Review, 668–677
- cartridge heater, 224, 514, 623
- CDR. See Critical Design Review
- CDRL. See Contract Data Requirements List
- chamber, 76, 167, 196, 335–338, 359, 500–501, 505, 508, 571, 651, 725–736, 745, 747, 748–754, 779–780
- charged particle radiation, 34, 36, 143, 145, 150–156, 169–170, 768
- Charon, 13, 48–50, 58–61
 - environments of, 58–60
- CHO-THERM, 276–280
- CIR. See Cargo Integration Review
- coating, 24, 81, 139–148, 158, 171, 176–180, 186, 214, 219, 317, 339, 356–357, 365, 399, 401, 483, 625–635, 655, 768–776
- compliant joint, 303, 307
- composite material, 81, 295, 299, 726, 729, 761–767
- concept definition phase (of spacecraft projects), 523–529
- conductance, 78, 85, 87, 115, 118–120, 161–162, 165, 209, 211, 248, 250–251, 254, 258, 260, 265–275, 284–290, 299–303, 308–320, 344, 347, 353–356, 359, 363–370, 390, 392, 394, 415, 442, 444, 445, 478–490, 492, 493, 503, 505, 507, 509–511, 514, 515, 516, 518, 533, 538, 543, 546, 547–548, 568, 571, 574, 577,

conductance (*continued*)

578, 581, 583, 596, 599, 601, 602, 615, 620,
622, 626–633, 639, 666, 719, 720, 726,
750, 763, 775, 779, 780, 786

conductivity

of materials, 803–813

of honeycomb, 813–818

conductor, 278, 353, 473, **544–552**, 563, 567,

568, 578, 581, 583, 654, 691, 696, 697, 766

contact conductance, 119, **247–318**, 320, 390,

392, 394, 451, 572, **599–638**, 605, 613,

615, 616, 617, 623, 626, 627, 628, 630,

631, 632, 633

contact resistance. *See* contact conductance

contamination, 98, **145–147**, 152, 154, 161,

167, 169, 174, 183, 187, 193, 196, 227,

275, 276, 447, 450, 478, 527, 530, 532,

756, 768, 772, 776

Contract Data Requirements List, 526

convection, 21, 91, 93, 198, 199, 201, 204, 248,

373, 406, 415, 419, 494, 507, **544–549**,

578, 581, 696–699, 705–706, 715, 756

CPL. *See* capillary pumped loop

Critical Design Review, 526, 531, 574, 721

declination, 38–45

degradation, 141, 143, 145, 152–158, 167, 223,

347, 356, 357, 397, 479, 489, 527, 557,

713–715, 727, 730, 768–771

density, of materials, 803–813

descending node, 38

design examples (thermal), 71–137

development test, 459, 531, 533, 536, 711, 712,

718, 725, 727, 746

differential expansion, 267, 290, 478, 727

diffusion, 295, 396, 418, 540–544, 552, 563,

567, 582–583, 589, 623, 752

diode heat pipe, **492–495**, 501, 719

dithering (of thermostats), 225, **227–228**

doublers, 72, 73, 100, 101, 209, 210, 247, **290–**

303, 320–321, 322, 532, 762, 765–767

Earth IR, **24–31**, 47, 66, 536, 555–563, 648,

666

Earth sensor, 2, 82

eccentricity, 7, **39–40**, 47, 52, 53, 56

eclipse, **40, 41, 45–48**, 51, 53, 54, 57, 63, 64,

66, 72, 73, 75, 81, 82, 87, 96, 98, 216, 241,

356, 555, 642, 666, 715, 722, 747

ecliptic plane, 36

effective emittance, 99, **161, 162, 164–167**,

169, 366, 551, 568, 654, 655, 776

electrical grounding. *See* grounding

emittance, 31, 49, 51, 54–56, 71, 72, 74, 81, 85,

86, 94, 95, 99, 100, 115, 117–122, 125,

139–144, 154, 161–169, 172, 173, 175–

179, 187, 194, 204, 207, 208, 219, 242,

331, 334, 336, 339, 347, 351, 355, 366,

482, 483, 485, 550, 551, 561, 563, 568,

593, 597, 651, 654, 655, 657, 661, 666,

768–786

of surface finishes, **139–144, 791–801**

energy balance, 139, 140, 207, 426, 429, 442,

481, 519, 585, 586, 715, 755

engineering compatibility assessment (for

space shuttle), 669

equatorial plane, 36, 38, 54

expendable booster, 7, 64, 66, 67

failure modes, 227, 505, 530, 532, 702

fasteners, 182–185, 284, 359–363, 532, 661

FDM. *See* finite-difference method

FEM. *See* finite-element method

ferry flight (for space shuttle), 701

fillers, 247, 257, 260

for contact interfaces, **274–284**

for phase-change materials, 306, 383, 384,

390–393, 394, 395, 397, 398, 400, 402

filters, 73, 339, 454, 458, 461, 463, 464, 552,

633, 677

finite-difference method, 269, 272, 293, 301,

302, 519, **576–586**, 587–591

finite-element method, 269, 272, 287, 288, 289,

293, 300, 301, 302, **586–590, 594**, 646–

648, 650

flat absorber, 139

flexible OSR. *See* surface finishes

flexible strap, 304–307

flight attitude, 678, 681, 687

flight history, 333, 354

floodlight, 674, 682, 685

fluid loop. *See* pumped fluid loop

FMH. *See* free molecular heating

foam insulation. *See* insulation, foam

FOSR (flexible optical solar reflector). *See* sur-
face finishes

free molecular heating, 21, 34, **32–34**, 63–66,
87

gasket, **275–284**, 307, 309

GEO. *See* geosynchronous orbit

geometric math model, 536, 561, 563, 686, 691,
696, 749

geosynchronous orbit, **10, 15, 16, 41, 45, 72,**

87, 150–152, 187, 341–344, 481, 766

GMM. *See* geometric math model

gravity assist, 11, 89, 501, 779

gray-body, 335, 550

grease, 275, 276, 602

grounding, 140, 141, **158–159**, 169, 176–177,

180, **186–188**, 191, 192, 196, 275, 278, 283

heat exchanger, 289, 376, 405, 406, 407, **424–**

431, 432, 442, 444, 458, 484, 507, 677, 685,

701, 702, 705, 708, 778

- heat pipe, 73, 78, 86, 209, 210, 211, 214, 217, 218, 219, 220, 247, 275, 284–289, 299–301, 304, 305, 353, 354, 374, 377, 382, 402, 405, 445, **489–505**, 507, 510, 511, 514, 516, 518, 532–534, 574, 719, 720, 725, 742, 744, 756, 760, 766, 767, 778, 779
- heat pump, 220, 481, 719, 786
- heat sink, 45, 71, 85, 291, 306, 353, 355, 363
- heat switch, **353–371**, 785–786
- heat transfer, 24, 85, 86, 93, 94, 95, 100, 124, 139, 142, 154, 162, 163, 164, 198, 199, 204, 247–250, 251, 253, 254, 255, 257–259, 261, 262, 264, 266, 268, 271–276, 281–284, 289, 291, 293, 301, 302, 304, 305, 306, 310, 312, 313, 316, 317, 320, 321, 322, 331, 335, 337, 347, 355, 363, 416, 418, 601, 602
- heater, 3, 66, 72, 74, 75, 77–79, 81, 82, 92, 93, 96, 100, 101, 102, 105, 107, 109, 112, 113, 115–119, 121, 122, 125–129, 131, 133–137, 143, 145, 209, 216, **223–245**, 349, 353–355, 367, 369, 660, 720, 753
- computer-controlled, 231–241
- radioisotope heater units, 241–245
- See also thermostats
- HMC. See Hydrogen Maser Clock
- honeycomb panel, 209, 216, 284, 288, 313, 516
- conductance of, 813–818
- Hubble Space Telescope, 19, 78, **95–137**, 170, 226, 227, 474, 502, 531
- Huygens probe, **87–95**, 199, 201, 202
- Hydrogen Maser Clock, 639, 640, **655–666**
- ICD. See interface control document
- IDEAS. See analysis codes
- indium tin oxide, 158, 171, 180, 187, 190, 769, 770
- insulation, 63, 64, 75, 77, 80, 81, 85, 92, 93, 94, 95, 109, 140, 154, **161–205**, 208, 335, 351, 374, 405, 446, 483, 523, 530, 534, 538, 540, 561, 562, 568, 572, 642, 694, 697, 708, 719, 756, 760, 775, 785
- aerogel, 161, 198, **201–203**, 785
- batt, **198–199**, 201, 204, 785
- foam, 93, 95, 145, 161, **199–201**, 204, 313, 335, 349, 390, 719
- gas void, **204–205**
- multilayer (MLI), 3, 61, 62, 63, 64, 72, 74, 75, 77, 80, 81, 82, 85, 92, 93, 94, 96, 98, 99, 100, 101, 105, 107, 109, 110, 112, 113, 114, 115, 117, 118, 119, 120, 121, 122, 124, 125, 127, 131, 133, 134, 135, 136, **161–197**, 198, 204, 211, 242, 245, 312, 336, 344, 357, 483, 523, 532, 560, 561, 562, 566, 567, 568, 583, 642, 644, 648, 649, 652, 654, 655, 657, 658, 662, 666, 697, 719, 760
- insulation blanket. See insulation, multilayer
- Integration Plan (for space shuttle), 669, 673–675, 678, 682, 685, 689, 701, 707, 708
- interface control document, 526, 669, 671, 674, 678, 682–685, 687, 691, 702, 704–706
- interplanetary trajectory, 60, 89, 534
- interstitial material, 276, 626
- IP (for space shuttle). See Integration Plan
- isolator, 77, 96, 122, 131, **310–313**, 451, 483, 532, 561, 567, 568, 571, 726, 767
- ITAS. See analysis codes
- ITO. See indium tin oxide
- joint resistance model, 603
- Jupiter, 11, 13, 49, 50, 58, 60, 61, 155, 158, 186, 241
- environments of, 58–60
- Kapton, 80, 94, 95, 99, 110, 114, 125, 127, 128, 140, 142, 144, 146, 148, 149, 151, 154–159, 161, 170–174, 176, 179, 180, 186, 187, 190, 194, 196, 201, 223, 237, 242, 279, 313, 335, 336, 349, 351, 652, 658, 765, 770, 785
- Lagrange points, 14
- launch/ascent, 32, 33, 91, 145, 173, 182
- environments of, 63–67
- launch site, 63, 161
- LDEF. See Long Duration Exposure Facility
- leak, 77, 85, 87, 94, 165, 167, 191, 208, 312, 351, 359, 447
- LHP. See loop heat pipe
- Long Duration Exposure Facility, 146, 148, 151, 155–158
- loop heat pipe, 209, 211, 214, **502–522**, 533, 780–782, 786
- louver, 78, 96, 100, 101, **331–352**, 365, 374, 405, 535, 574, 719, 725, 744, 760, 772, 774–776
- low Earth orbit, 7, 9, 18, 22, 40, 44, 87, 146, 156, 158, 180, 182, 185, 186, 208, 557, 770
- environments of, 21–32
- MAR. See middeck accommodations rack
- Mars, 11–13, 49, 50, 204, 306, 313, 353, 447, 459, 465, 467, 725, 760, 777, 780, 785, 786
- environments of, 56–58
- Mars Pathfinder, 214, 406, 724, 760, 777
- pumped fluid loop on, 444–468
- material compatibility, 460, 500
- MEMS. See microelectromechanical systems
- Mercury, 13, 48–54, 474
- environments of, 50–52
- microelectromechanical systems, 772, 775–778, 786
- micrometeoroid, 140, 155, 161, 170, 187–190, 357, 532

- middeck accommodations rack (of space shuttle), 707–708
- middeck environment (of space shuttle), 698
- MIL-HDBK-340A. See standards
- MIL-STD-1540. See standards
- MIL-STD-1540B. See standards
- MIL-STD-24236. See standards
- MLI. See insulation, multilayer
- Molniya orbit, 3, 10, 47, 48
- monogroove heat pipe, 490–491
- moon, 11, 13, 14, 22, 46, 48, 49, 53–55, 87–89, 353, 375
- mounting, 77, 83, 89, 100, 101, 105, 109, 116, 118, 122, 124, 211, 245, **247–349**, 356, 360, 363, 452, 478, 479, 552–556, 561, 566–568, 626, 646, 649, 652, 656, 662, 664, 666, 697, 716, 717, 720, 726, 729, 731, 732, 739, 744
- MPF. See Mars Pathfinder
- multilayer insulation. See insulation, multilayer
- navigation, 15–17, 61, 153, 467, 655
- Neptune, 1, 3, 49, 50, 60, 61, 379
 - environments of, 58–60
- NEVADA. See analysis codes
- node, 38, 40, 114, 227, 344, 346, 444, 535–538, **539–544**, 545–552, 563, 566, 567, 568, 576–584, 587, 588, 589, 590, 650, 661, 686, 691–697, 749, 751
- optical solar reflector. See surface finishes
- optical system, 226, 481, 639, 640
 - analysis of, 644–651
- orbit, 15–48, 375, 376, 406, 481, 501, 512, 523, 529, 532–537, 552, 553–558, 560–563, 571, 591, 594, 595, 641, 642, 648, 666, 673–675, 678, 683, 685, 687, 688, 690, 702, 704, 706, 711, 715, 718, 722, 728, 729, 737, 747, 751
 - parameters 7, 11, 13, **36–45**, 49, 346, 591
 - types of, **7–14**
- OSR (optical solar reflector). See surface finishes
- packaging, 381, 382, 397, 516, 528, 761, 763, 764, 766, 776, 782
- paint. See surface finishes
- pallet, 1, 3, 678, 727
- paraffin, 180, 211, 353, 357–359, 363–365, 378, 400
- PCM. See phase-change material
- PDR. See Preliminary Design Review
- Peltier cooler. See thermoelectric cooler
- PFL. See pumped fluid loop
- phase-change material, 373, 405 85, **373–402**, 783, 533, 784, 786
- pinwheel louver. See louvers
- planetary flyby, 48, 50
- platform, 1, 15, 91, 93, 95, 124, 286, 502, 591, 592
- Pluto, 13, 48, 49, 50, 58, 60, 61, 92, 93
 - environments of, 58–60
- POAM. See Polar Ozone and Aerosol Monitor
- Polar Ozone and Aerosol Monitor, 552–571
- precision temperature control, 639–666
- prelaunch environment, **63**, 581
- Preliminary Design Review, 529–531, 574
- propulsion system, 3, 7, 73–75, 523, 530, 536, 640, 710, 724, 729, 760, 777
- pump law, 423
- pumped fluid loop, 209, 211, 214, 215, 220, 355, 377, 405–472, 719, 777
- pumps, 214, 215, 220, 407, 418–424, 443, 447, 448, 451, 453, 457, 465, 473, 475, 481, 496, 503, 574, 708, 719, 752, 756, 760, 777, 786
- qualification test, 457, 458, 530, 711, 712, 714, 717, 722, 723, 724, 728, 730, 731, 734, 737, 744, 746
- quartz mirror. See surface finishes
- radiation,
 - effect on materials, 146, 150–151
 - thermal, analysis of, 592–596
- radiation analysis, 592
- radiation shield, 114, 142
- radiator, 18, 22, 24, 25, 31, 34, 36, 55, 59, 71, 72, 73, 75, 78, 79, 82, 84, 85, 86, 100, 101, 105, 107, 109, 114, 141, 142, 143, 145, 152, 161, 183, 197, **207–221**, 284, 310, 331, 336, 338–344, 346, 347, 349, 351, 352, 354–357, 363–366, 374–377, 380–388, 392, 400, 402, 405–407, 446–452, 459, 465, 466, 475, 478, 481–487, 495, 501, 507, 508, 519, 524, 528, 530, 533, 537, 552, 556, 557, 560, 562, 566, 568, 626, 648, 682–684, 702, 714, 715, 719, 720, 725, 750, 755, 760–769, 772, 775, 779, 780, 782, 784, 786
- radiator module (with heat switch), 363–365
- radioisotope heater unit, 92, 93, **241–245**
- remote sensing, 15
- Request For Proposal, 526–528
- RFP. See Request For Proposal
- RHU. See radioisotope heater unit
- right ascension, 38–43
- room-temperature-vulcanized fillers, 275, 283, 284, 322
- RTV fillers. See room-temperature-vulcanized fillers
- Saturn, 11, 13, 49, 50, 87–89, 93, 158, 186
 - environments of, 58–60
- SDR. See System Design Review
- seam, 165, 166, 167, 176, 180, 181, 191, 192, 195, 196, 197, 396
- second-surface mirror. See surface finishes

- semimajor axis, 13, 39, 40, 49
- set point, 105, 107, 109, 113, 115, 118, 126, 128, 133, 134, 136, 137, 224–232, 240, 242, 333, 351, 354, 356, 358, 365, 448, 516, 517, 660–665, 678, 719
- shape factor, 550
- silvered Teflon. See surface finishes
- SINAPS. See analysis codes
- SINDA. See analysis codes
- SOAP. See analysis codes
- solar absorber, 139
- solar array, 1–3, 22, 62, 64, 66, 71, 72, 81, 85, **86–87**, 88, 125, 129, 131, 313, 485, 534, 557, 562, 566, 568, 729, 749
- solar entrapment (on space shuttle), 678, 679, 697
- solid-rocket motor, 73, 76, 77, 161
- solid-state controller, 75
- SOW. See Statement of Work
- space shuttle, 3, 7, 66, 96, 101, 131, 146, 155, 213–215, **667–708**
- spacer, 87, 135, 161, 162
- specific heat, 201, 214, 255, 303, 322, 379, 380, 384, 392, 429, 432, 442, 449, 544, 567, 575, 596, 655
 - of materials, **803–813**
- spin-stabilized spacecraft, 1
- spray cooling, 784–785
- SRR. See Systems Requirement Review
- SSPTA. See analysis codes
- standards, 531, 592, 669, 686, 711, 722, 731, 737, 739, 740, 745
 - MIL-HDBK-340A, 527, 709
 - MIL-STD-1540, 572, 709, 710, 718, 728, 732
 - MIL-STD-1540B, 709, 716, 732, 737, 744
 - MIL-STD-24236, 527
- star sensor, 2, 81, 474
- Statement of Work, 526–528
- structural analysis, 587
- sun day angle, 36, 44
- sunlight, 21, 22, 24, 25, 30, 40, 48, 83, 87, 91, 139, 142, 144, 152, 155, 166, 170, 186, 187, 245, 332, 341, 346, 347, 367, 552, 557, 571, 642, 687
- sunshield, 333
- sun-synchronous orbit, 9, 10, 16, 43, 552, 553, 555
- surface finishes, 3, 83, 92, 94, 96, 98, 99, 112, 114, 115, 129, 131, 139, 144, 152, 155, 158, 165, 166, 167, 170, 207, 223, 258, 265, 266, 355, 382, 485, 487, 530, 534, 557, 561, 648, 719, 727
 - flexible optical solar reflector (FOSR), 768–770
 - optical solar reflector (OSR), 85, 139, 140, 141, 143, 144, 146, 151, 152, 154, 158, 159, 207, 214, 336, 485, 719, 768–770
 - paint, 54, 71, 78, 80–82, 86, 87, 94, 98, 99, 113, 120, 122, **140–148**, **154**, 156, 158, 170, 207, 216, 242, 245, 336, 347, 348, 357, 451, 532, 550, 561, 651, 719, 768–772
 - quartz mirror. See optical solar reflector
 - second-surface mirror. See optical solar reflector
 - silvered Teflon, 98, 100, 105, 107, 109, 113, 125, 127, 128, **144**, 151, **153**, 157, 158, 159, 170, 347, 557, 558, 560, 770
 - table of surface properties, **144**, **791–801**
 - TiNOX, 142, 144
 - vapor-deposited aluminum (VDA), 142, 144, 172
 - white paint, **81**, **86**, **139–141**, **148**, **154**, **158**, 207, 347, 348, 357, 768–772
- surveillance missions, 9, 10, 15, 17, 18
- System Design Review, 526
- System Requirements Review, 526
- TAS. See analysis codes
- TEC. See thermoelectric cooler
- technology projections, 523, **759–829**
- technology readiness, 776
- test data, 165, 166, 194, 302, 336, 337, 338, 343, 347, 348, 361, 443, 519, 536, 571, 572, 615, 651, 716, 748, 750, 751, 765
- testing, 63, 96, 114, 148, 161, 189, 196, 199, 215, 216, 227, 245, 254, 335, 338, 351, 355, 359, 366, 446, 448, 453, 460, 461, 478, 480, 485, 487, 489, 490, 491, 498, 500, 503, 523, 528, 530, 531, 533, 535, 536, 570, 572, 644, 662, 706, **709–758**, 761, 767, 771
- thermal balance test, 355, 487, 501, 531, 533, 534, 570–572, 574, 715, 718, 721, **725–726**
- thermal cycle, 156, 453
- thermal cycle test, 713, 714, 717, 730, 732, 733, 736–740, 743
- thermal design, 1, 11, 14, 30, 34, 45, 46, 62, 63, 64, 66, 139, 161, 167, 187, 195, 223, 247, 266, 284, 339, 340, 354, 355, 425, 482, 639, 640, 642, 666, 675, 679, 681, 684, 685, 686, 690, 691, 715, 721, 723, 724, 728, 746, 747, 759, 760, 761, 769
 - examples, **71–137**
 - analysis, **523–598**
- Thermal Desktop. See analysis codes
- thermal finish. See surface finishes
- thermal math model, 275, 281, 284, 293, 525, 533, **535–538**, **544**, **561–568**, **570**, **571**, **572**, **574**, **575**, **590**, 682, 686, 690–697, 748
- thermal modeling, 287, 537–552, 567, 592
- thermal vacuum test, 196, 359, 452, 457, 459, 465, 467, 531, 570, 651, **709–717**, **725–739**, **743–751**
- THERMICA. See analysis codes
- thermoelectric cooler, 405, 473–487, 514, 719

- thermostat, 75, 78, 100, 101, 102, 105, 109, 112, 113, 118, 126–129, 131–134, 136, 137, **223–231**, 241, 353, 516, 527, 530, 533, 574, 639, 719, 720, 725, 744
- three-axis-stabilized spacecraft, 1, 3
- thruster, 1, 61, 66, **73–76**, 142, 146, 224, 225, 234, 235, 237, 310, 710, 729
- TiNOX. See surface finishes
- TMM. See thermal math model
- transfer orbit, 7, 11, 66, 73, 77
- TRASYS. See analysis codes
- TSS. See analysis codes
- twelve-hour orbit, 47, 66
- upper stage, 7, 8, 66, 479, 527, 533
- Uranus, 13, 49, 50, 60, 61
 - environments of, 58–60
- validation, 523, 525, 526, 640, 711, 721, 725
- vapor-deposited aluminum. See surface finishes
- variable conductance, 359, 516, 719, 720
- variable conductance heat pipe, 489, 492, 495, 496, 502, 510, 533, 719–720, 779
- variable radioisotope heater units (VRHU), 241–245
- VCHP. See variable conductance heat pipe
- VDA (vapor-deposited aluminum). See surface finishes
- velocity control, 2
- vendors, 103, 169, 171–186, 189, 452, 453, 475, 476, 480, 486
- venting, 98, 152, 173, 182, 201, 447, 450, 467, 532
- Venus, 11–13, 49, 52, 53, 89, 91
 - environments of, 52–53
- view factor, 24, 55, 339, 356, 485, **549–552**, 593, 654, 697, 714, 718, 749, 750
- VRHU. See variable radioisotope heater units
- wavelength, 20, 22, 24, 31, 32, 139, 146, 147, 202, 593, 595, 596, 608, 634, 726, 753–755, 768–770, 773, 776
- white paint. See surface finishes
- wick, 489–515, 520, 778–780, 786
- working fluid, 406, 419, 432, 443, 447, 448, 499, 451, 453, 454, 461, 465, 467, 490, 494, 496–498, 500, 506–509, 511, 518, 720, 777, 778, 780